

Features:

- ◆ 1920*1080 HD Video output
 - ◆ 1/2.7"GC2033 CMOS Sensor
 - ◆ AGC, AWB, DPC, DWDR, Super 2D-DNR
 - ◆ Use traditional CCTV coaxial cable transmission
- The maximum transmission distance up to 500 meters



Model No.	YE-HD20000BFL
Image Sensor	1/2.7" GC2033 CMOS Sensor
Scanning System	2:1 Interlace
System	PAL/NTSC
Total Pixel	1920*1080P
Min. Illumination	0.0005Lux@F1.2, 0Lux (IR ON)
S/N Ratio	≥ 52dB
Video Output	AHD mode
Gamma Correction	0,45
Sync. System	Internal Synchronization
Day&Night	Color/Auto/B/W/EXT
Shutter Speed	1/25 -1/45,000s
White Balance	Auto
AES	Auto
DPC	Auto
BLC	BLC/HLC/OFF
A.G.C	Auto
DWDR	ON/OFF
Noise Reduction	Super 2D-DNR
Lens	3.6mm fixed lens
LED	4pcs Array LED
IR Distance	60M
Casing Material	Metal
Weight	0.7kg
Power Supply	DC12V±5 %
Humidity	≤ 85%RH
Operation Temp.	-20℃~+50℃